

LANSDALE

VALVE & MANUFACTURING


1040 Broadway Westville, NJ 08093 / Phone: (800) 908-0523 / Fax: (856) 456-9223 / www.gemfiresprinkler.com

BALL VALVE

Full Port

- Full-Port threaded ends
($\frac{1}{4}$ " to 2" with CSA/UL/FM/NSF61 Approval)
- 2-Piece Forged Brass
- Female NPT Inlet and Outlet
- 600 WOG (2 $\frac{1}{2}$ " TO 4": 400 WOG/600WOG Optional), 150 SWP
- Valves conform to Federal Specifications WW-V-35, Type II Class A, Style 3 and MSS SP-110

SIZE	D	W	H	L
1/2"	0.50"	2.12"	1.45"	3.23"
3/4"	.75"	2.41"	1.78"	3.94"
1"	0.98"	2.96"	2.29"	4.72"
1-1/4"	1.22"	3.28"	2.44"	4.72"
1-1/2"	1.50"	3.67"	3.00"	7.09"
2"	1.97"	4.21"	3.30"	7.09"




UL Approval

- Trim and Drain (300 psi)
- Compressed Gas Shut-off Valves (600 psi)
- Flammable Liquid Shut-Off Valves (600 psi)
- Gas Shut-Off Valves (600 psi)
- LP-Gas Shut-Off Valves (600 psi)
- Manual Valves (600 psi)



FM Approval

- 600 psi rating



MATERIAL LIST		
NUMBER	DESCRIPTION	MATERIAL
1	Body	Forged Brass
2	End Cap	Forged Brass
3	Ball	Brass
4	Seat	PTFE
5	Stem	Brass (ASTM B16)
6	Thrust Washer	PTFE
7	Packing	PTFE
8	Gland	Brass
9	Handle	Carbon Steel Plated
10	Nut	Carbon Steel Plated

PROJECT		APPROVAL STAMP
PROJECT:		<input type="checkbox"/> APPROVED
ADDRESS:		<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:		<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:		REMARKS:
NOTES 1:		
NOTES 2:		

Revision: 1/2019