

## BRASS GLOBE VALVE SOFT SEAT 200 PSI


MODEL LVBGV





## **FEATURES:**

- Working Pressure: 200 WOG
- Threads to ANSI B1.20.1 (NPT)
- Intended for use in fire protection systems and non-potable plumbing systems



SIZE (In.)	D (ln.)	H (ln.)	L (ln.)
1/4	2.17	2.32	1.77
1/2	2.17	2.85	1.89
3/4	2.17	2.93	2.17
1	2.56	3.43	2.48
1-1/4	1.68	4.08	2.91
1-1/2	2.95	4.89	3.31
2	3.35	5.38	3.94

NOMENCLATURE & MATERIAL LIST					
NUMBER	DESCRIPTION	MATERIAL	SPEC. ASTM		
1	Body	Cast Brass	B584 C85700		
2	Seat Screw	Brass Rod	B111 C28000		
3	Washer	Stainless Steel	S.S.304		
4	Seat	NBR			
5	Disc Holder	Brass Rod	B16 C36000		
6	Bonnet	Forged Brass	B124 C3700 (1/4"~1")		
		CAST BRASS	C85700 (1½"~2")		
7	Packing Nut	Brass Rod	B16 C36000		
8	Packing	Teflon	PTFE		
9	Packing Gland	Brass Rod	B16 C36000		
10	Handwheel	Cast Iron	A48 CLASS/NO. 30		
11	Nameplate	Aluminum	COMMERCIAL		
12	Handwheel Nut	Steel	A29.GR1010		

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	☐ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	