

FIRE DEPARTMENT CONNECTION PLASTIC BREAKABLE CAPS 2½” MODEL LVBCP



DESCRIPTION:

Plastic Breakable caps provide protection against the introduction of foreign material into the swivels but allow for quick access when a hose connection is necessary.

The Plastic Breakable Caps for Fire Department Connections are injection molded polystyrene. Each set includes two caps and 4 eyelets with nuts for 2½” swivels. The caps have been molded with “scored” tabs for easy removal with a hydrant wrench or other similar tool.

INSTALLATION:

Remove the caps from their packaging. Hold the breakable cap to the opening of swivel. Align the breakable tabs with the pin lugs on the swivel. Insert the threaded end of one eyelet through the hole in the tab of the cap then once aligned, slide the eyelet over the pin lug. Once the eyelet is in place, carefully thread the included 1/4 -20 finished hex nut onto the threaded end of the eyelet until snug.

Material: Injection Molded Polystyrene

Size: 2½” Swivel

Type: Pin Lug

Included per set: (2) caps, (4) eyelets, (4) hex nuts

| PROJECT | APPROVAL STAMP |
|-----------------|--|
| PROJECT: | <input type="checkbox"/> APPROVED |
| ADDRESS: | <input type="checkbox"/> APPROVED AS NOTED |
| ENGINEER: | <input type="checkbox"/> NOT APPROVED |
| SUBMITTAL DATA: | REMARKS: |
| NOTES 1: | |
| NOTES 2: | |

BREAKABLE CAPS METAL 2½"

MODEL LVBCM



DESCRIPTION

The Metal Breakable Caps for Fire department Connections are cast aluminum. Each set includes two caps and 4 eyelets with nuts for 2½" swivels. The caps have been molded with "scored" tabs for easy removal with a hydrant wrench or other similar tool. Metal Breakable caps provide inexpensive protection against the introduction of foreign material into the swivels but allow for quick access when a hose connection is necessary.

Installation:

Remove the caps from their packaging. Hold the breakable cap to the opening of the swivel. Align the breakable tabs with the pin lugs on the swivel. Once aligned, insert the threaded end of one eyelet through the hole in the tab of the cap then slide the eyelet over the pin lug. Once the eyelet is in place, carefully thread the included 1/4 -20 finished hex nut onto the threaded end of the eyelet until snug.

Material: Cast Aluminum

Size: 2½", 3"

Type: Pin Lug

Color: Red, Green, Yellow

Included per set: (2) caps, (4) eyelets, (4) finished hex nuts

*Available in sets only

****Caution: Do not over tighten. The tabs of the break caps are designed to break with minimal force.**

| PROJECT | APPROVAL STAMP |
|-----------------|--|
| PROJECT: | <input type="checkbox"/> APPROVED |
| ADDRESS: | <input type="checkbox"/> APPROVED AS NOTED |
| ENGINEER: | <input type="checkbox"/> NOT APPROVED |
| SUBMITTAL DATA: | REMARKS: |
| NOTES 1: | |
| NOTES 2: | |