

LANSDALE

VALVE & MANUFACTURING

1040 Broadway Westville, NJ 08093 / Phone: (800) 908-0523 / Fax: (856) 456-9223 / www.gemfiresprinkler.com

Standpipe Equipment

90° EXPOSED SIAMESE

SINGLE CLAPPER

4" x 2½" x 2½"



The 90 Degree Fire Department Connection is manufactured from solid brass* components to increase service life. The single clapper design features brass clapper and brass seats within a cast brass body. The 2½" inlets are pin lug design for ease of use and compatibility with local fire service districts. Swivel gaskets are included.

*Contains lead. Not for use in consumption water systems intended for humans. Available for NST pin lugs.

INSTALLATION

Installation of the Fire Department Connection is achieved with readily available been installed on the nipple. Coat male threads of 4" IPS nipple liberally with a suitable pipe thread sealant such as Pipe Fit®. Tighten FDC one full turn past hand tight. Make sure FDC is aligned according to requirements.

DO NOT OVER TIGHTEN. OVER TIGHTENING MAY CAUSE SEVERE STRETCHING AND POSSIBLE CRACKING OF THE OF THE FDC BODY.

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 1/2019