


# ZINC FLANGE PACKS

## MODEL LVFP



Both ring and full face gaskets are available for ASTM CL 150 and 300 Flanges

### DESCRIPTION:

Flange Packs include everything needed to make-up a flanged assembly. Each kit includes one 1/8" red rubber ring or full face gasket and the correct number of plated hex head bolts and nuts per flange.

### SPECIFICATIONS:

- Each kit contains one 1/8" thick red rubber ring gasket meeting ASTM D-1330 CL-125/150 and the following ASTM A307 plated bolts and ASTM A563 GR A hex nuts according to size
- 1/8" thick either Ring or Full Face per ANSI/AWWA C110/A21.10 and ANSI/AWWA C111/A21.11
- Temp. Range: Max. 170°F (77°C)  
Min. -20°F (-29°C)
- Max. Pressure: 150 PSIG

CLASS 150		
SIZE (in.)	NO. OF BOLTS	BOLT SIZE (in.)
2	4	5/8 x 2-1/2
2-1/2	4	5/8 x 3
3	4	5/8 x 3
4	8	5/8 x 3
5	8	3/4 x 3-1/2
6	8	3/4 x 3-1/2
8	8	3/4 x 3-1/2
10	12	7/8 x 4
12	12	7/8 x 4
14	12	1 x 4-1/2
16	16	1 x 4-1/2
18	16	1-1/8 x 5
20	20	1-1/8 x 5
24	20	1-1/4 x 5-1/2
30	28	1-1/4 x 6-1/2
36	32	1-1/2 x 7
42	36	1-1/2 x 7-1/2
48	44	1-1/2 x 8

CLASS 300		
SIZE (in.)	NO. OF BOLTS	BOLT SIZE (in.)
2	8	5/8 x 3
2-1/2	8	3/4 x 3-1/4
3	8	3/4 x 3-1/2
4	8	3/4 x 3-3/4
5	8	3/4 x 4-1/4
6	12	3/4 x 4-1/4
8	12	7/8 x 4-3/4
10	16	1 x 5-1/2
12	16	1-1/8 x 5-3/4
14	20	1-1/8 x 6-1/4
16	20	1-1/4 x 6-1/2
18	24	1-1/4 x 5-3/4
20	24	1-1/4 x 7-1/4
24	24	1-1/2 x 8

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	