

# LANSDALE

## VALVE & MANUFACTURING

# BRASS INLINE CHECK VALVE

**Model Number: LV-ICV**

**Features:**

**Size Range:** 1 " through 2"

**Working Pressures:** 200 WOG

**Testing Pressure:** Shell 80 PSI AIR, Seat 80 PSI AIR


**Remarks:** Threads to ANSI B1.20.1 (NPT)

- Cast brass body
- Forged brass poppet provide extra strength
- Valves can be installed in horizontal or vertical position
- 304 stainless steel springs
- Non-corrosive Nylon stem guide assures smooth, noise free valve operation
- Abrasion-resistant neoprene O-ring is precision fitted to the poppet for positive seal into the tapered self-clean valve seat



SIZE	A	B
1"	80	44
1 1/4"	92"	54
1 1/2"	102	60
2"	128	76

NUMBER	PART NAME	MATERIAL	SPEC. ASTM
1	Body	Cast Brass	B584 C85700
2	Disc	Forged Brass	B124 C37700
3	Nut	Stainless Steel	S.S.304
4	Spring Cover	Stainless Steel	S.S.304
5	Spring	Stainless Steel	
6	Disc Guide	Nylon	
7	O-Ring	NBR	



### \*\*WARNING: DO NOT OVER TIGHTEN

Over tightening during installation will crack the valve body. Evidence of over tightening may not be readily visible or apparent upon pressurization.

PROJECT		APPROVAL STAMP
PROJECT:		<input type="checkbox"/> APPROVED
ADDRESS:		<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:		<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:		REMARKS:
NOTES 1:		
NOTES 2:		