

1040 Broadway Westville, NJ 08093 / Phone: (800) 908-0523 / Fax: (856) 456-9223 / www.gemfiresprinkler.com

## **POST INDICATOR VALVE**

## with FLANGE ENDS


## **Model Numbers:**

4" 700-275-00020 6" 700-275-000400 8" 700-275-00060

10" 700-275-00065 12" 700-275-00075

## **General Specifications:**

- Valves comply with AWWA C515-15 Standard
- Non-Rising Stem, resilient seated (EDPM encapsulated wedge)
- Triple O-Ring Seal
- Available with optional test plug on valve body (special order)
- Post Indicator Valves provided with universal "Indicator Post Plate"
- Mechanical joint ends to AWWA C153/A21.53
- Flanged Ends to ANSI B16.1, CLASS 125
- UL/Listed/FM Approved at 300 PSI water working pressure rating
- NSF-61 and NSF-372 certified as lead-free for use in drinking water systems
- Temperature Range: 42°-180° F
- Fusion bonded epoxy coated interior and exterior to AWWA C550 standard
- Flanged Valves available with hand wheel or operating nut





MATERIAL SPECIFICATIONS						
PART	MATERIAL	ASTM SPEC.				
Body	Ductile Iron	A536 65-45-12				
Wedge	Ductile Iron	EPDM Encapsulated				
Wedge Nut	Bronze	B62 C83600				
Stem	Stainless Steel	ISI 304				
Bonnet	Ductile Iron	A536 65-45-12				
Gasket	Rubber	EPDM				
Gland	Ductile Iron	A536 65-45-12				
Thrust Collar	Bronze	B62 C83600				
0-Ring	Rubber	EPDM				
Post Flange	Ductile Iron	A536 65-45-12				
Operating Nut	Ductile Iron	A536 65-45-12				
NPT Plug	Bronze	Commercial				
Post Flange	Bolt	Stainless Steel AISI 316				
Bonnet Bolt	Stainless Steel	AISI 304				

VALVE DIMENSIONS									
Size	3"	4"	5"	6"	8"	10"	12"		
L	8	9"	10"	10½"	11½"	13	114		
Н	11%"	13¾"	161⁄8"	17 <sup>5</sup> /16	21 <sup>7</sup> / <sub>16</sub>	25%"	28 ¾"		
D		12"	12"	12"	12"	12"	12"		
Weight lbs.	41	64	79	103	161	235	339		

PROJECT	APPROVAL STAMP
PROJECT:	□ APPROVED
ADDRESS:	□ APPROVED AS NOTED
ENGINEER:	□ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 1/2019