

RISER PAK

MODEL LVRPAK



DESCRIPTION:

- Preassembled for ease of installation
- Can be supplied with test and drain or ball valve as required
- Butterfly valve has built in tamper switch
- Compact design
- Test and drain with optional PRV, available nominal K-Factor: 2.8, 4.2, 5.6, 8.0, 11.2, 14.0 (available on 1-1/4" - 2" size units only), and 25.2 (available on 1-1/2" and 2" size units only)
- All components are UL Listed and FM Approved
- Can be installed both vertically and horizontally. See O&M manual for additional information.

RISER PAK		
SIZE (in.)	OVERALL LENGTH (in.)	OVERALL DEPTH (in.)
2	24.3	12
2-1/2	24.8	13.3
3	25.2	14
4	27.2	16
6	30.3	19.5
8	32.3	24.75

PRESSURE DROP EXPRESSED IN EQUIVALENT LENGTHS OF Sch 10 PIPE	
SIZE (in.)	C=120
2	16.6
2-1/2	14.0
3	16.3
4	20.1
6	21.8
8	28.5

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	