

WAFER CHECK VALVE 300 PSI


MODEL LVWCV

UL US FM APPROVED
EX26984



FEATURES:

- The extremely short face to face dimension and compact design of this valve allow installation and service in tight spaces.
- Spring assisted for better dynamic behavior
- Soft seated for perfect tightness even at low differential pressure
- Can be installed vertically or horizontally
- Flanges to ANSI B16.1 CLASS125
- Working Pressure 300 PSI
- Working Temperature -10°C to 82°C
- Spray-painted or fusion bonded epoxy coated interior and exterior to AWWA C550 standard for corrosion protection



MATERIAL SPECIFICATION		
DESCRIPTION	MATERIAL	ASTM Spec.
Body	Ductile Iron	ASTM A536 65-45-12
Disc	Bronze	C83600
Seat	Bronze	C83600
Shaft	Stainless Steel	AISI 304
Spring	Stainless Steel	AISI 304
Stop Collar	Stainless Steel	AISI 304
O-Ring	EDPM	EDPM
Set Spring	Stainless Steel	
NPT Plug	Carbon Steel	AISI 304

DIMENSIONS (MM/IN)						
SIZE	100 mm / 4"		150 mm / 6"		200 mm / 8"	
	mm	inch	mm	inch	mm	inch
L	108	4.25	95	3.74	95	3.74
D	174.2	6.86	215.9	8.5	279.4	11.0

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	