

1040 Broadway Westville, NJ 08093 / Phone: (800) 908-0523 / Fax: (856) 456-9223 / www.gemfiresprinkler.com

BREAKABLE CAPS METAL

2½" 350-125-01800

DESCRIPTION:

The Metal Breakable Caps for Fire department Connections are cast aluminum. Each set includes two caps and 4 eyelets with nuts for 2½" swivels. The caps have been molded with "scored" tabs for easy removal with a hydrant wrench or other similar tool. Metal Breakable caps provide inexpensive protection against the introduction of foreign material into the swivels but allow for quick accesswhen a hose connection is necessary.

INSTALLATION:

Remove the caps from their packaging. Hold the breakable cap to the opening of swivel. Align the breakable tans with the pin lugs on the swivel. Once aligned, insert the threaded end of one eyelet through the hole in the tab of the cap then slide the eyelet over the pin lug. Once the eyelet is in place, carefully thread the included 1/4 -20 finished hex nut onto the threaded end of the eyelet until snug.

Material: Cast Aluminum

Size: 2½", 3" **Type:** Pin lug

Color: Red, Green, Yellow

Included per set: (2) caps, (4) eyelets, (4) finished hex nuts

*Available in sets only



Caution: Do not over tighten. The tabs of the break caps are designed to break with minimal force.

PROJECT	APPROVAL STAMP
PROJECT:	□ APPROVED
ADDRESS:	□ APPROVED AS NOTED
ENGINEER:	□ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 1/2019