

www.lansdalevalve.com

BRECOIL - Cutting Oil

BRECOIL features a well-balanced blend of active sulfur and chlorine to produce dark, semi-transparent cutting fluid for threading cutting and most other machining of high brinell metals, gear stocks and stainless steel. BRECOIL is a medium viscosity cutting oil designed to handle tough machining operations. This cutting fluid is FBC System Compatible with FlowGuard Gold, BlazeMaster and Corzan CPVC piping systems.

PHYSICAL AND CHEMICAL PROPERTIES:

Vapor pressure: <0.1 mmHg at 20°C (68°F).

API gravity: 23.5 15.6°C (60.0°F). Density: Not determined.

Specific gravity: 0 0.913 @ 15.6°C (60°F)

Solubility: Negligible in water, miscible in most petroleum solvents.

Percent volatile: Negligible.

Vapor density (air=1): >1.

Evaporation rate (n-Butyl Acetate=1): Negligible.

Odor: Sharp sulfur odor.

Appearance: Dark brown to black in color.

Viscosity: ~25 cSt @ 40°C



AVAILABLE IN:

1 gallon Jugs 5 Gallon Bucket 55 Gallon Drum



APPROVED

*FBC TM System Compatible indicates this product has been tested by Lubrizol Advanced Materials and is monitored on an ongoing basis to assure chemical compatibility with FlowGuard Gold, Blaze Master, and Corzan pipe and - fittings.

The information contained herein is believed to be reliable but is for guidance only. Brecco Distribution and its agents cannot assume liability for results obtained in the use of its products by the persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Data:	
Notes 1:	
Notes 2:	