

1040 Broadway Westville, NJ 08093 / Phone: (800) 908-0523 / Fax: (856) 456-9223 / www.gemfiresprinkler.com

PRESSURE RESTRICTING ANGLE VALVE







WITH HYDROLATOR

FEMALE NPT INLET X FEMALE NPT OUTLET


1½" F x FNST 350-125-01130

2 1/2" M x FNST 350-125-01132

2 1/2" M x FYFD 350-125-01134



300 lb (2070 KPa) pressure tested approved valve. Heavy Duty 1-1/2" (38 mm) pressure restricting angle hose and hydrolator valve. Automatically drains and vents, safeguarding against hose deterioration. O-ring packing and red cast handle. Forgeline Bonnett and Seat Assembly. Water pressure is controlled by adjustable flow restriction. If full flow is required, the restriction may be overridden. Furnished with field setting chart. Contains lead. Not for use in water systems intended for human consumption.



A = 4" (100 mm)

 $B = 2 \frac{1}{4}$ " (56mm)

C = 8" (OPEN) (200mm)

C = 7" (CLOSED) (175mm)

WEIGHT: 5.05 lbs (2.30Kg)

WORKING PRESSURE: 300 lb (2070 Kpa)



PROJECT	APPROVAL STAMP
PROJECT:	□ APPROVED
ADDRESS:	□ APPROVED AS NOTED
ENGINEER:	□ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	

Revision: 1/2019