

**Complete Grooved System for All Your Fire Protection Needs** 



## **TABLE OF CONTENTS**

Grooved Piping System	2
GemLock® Features	3
Rigid Coupling - Style 5	4
Rigid Coupling Angle Pattern - Style 5A	5
One-Bolt, Push-on Coupling - Style 99	6
Flexible Coupling - Style 12	7
Reducing Coupling - Style 25	8
Flange Adapter - Style F190	9
Grooved Flange - Style 14	10
Flange Adapter Insert - Style 20	11
Mechanical Tee Grooved - Style 15	12
Mechanical Tee Threaded - Style 35	13
Mechanical Tee Grooved - Style 16	14
Mechanical Tee Threaded - Style 36	15
Tee Lock - Style 13	16
Tee Lock - Style 13A	17
Grooved Fittings - Short Pattern - Styles F105, F106, F107, F135	18
Standard Grooved Fittings - Styles 100, 101, 102, 103, 110, & 150	19
Reducing Tee - Short Pattern - Style 115	20
Standard Reducer - Style 140 Concentric - Style 145 Eccentric	21
Standard Drain Elbow - Style F100D, F105D & Drain Tee - Style 115D	22
Standard Drain Cap - Style F155D	23
90º Adapter Ell - Style 105TL	24
Lansdale® Grooved End Swing Check Valve - Model LVCVGG-400	25
Lansdale® Grooved End Check Valve w/Inspection Cover - Model LVCVGG-RF	26
Lansdale® Riser Check Assembly (Shot Gun Riser) - Model LVRCGG	27
Lansdale® Grooved Butterfly Valve - Model LVBG1 & LVBG3	28
Lansdale® Power Ball 300	29
PI Tape Instructions	30
Pipe Preparation/Pipe Grooving Specifications	31
Rigid Coupling - Style 5 & Flexible Coupling - Style 12 Installation Instructions	32
One-Bolt, Push-on Coupling - Style 99 Installation Instructions	33
Mechanical Tee Installation Instructions	34
Gasket Data	35
Cross Reference Chart	36
Terms and Conditions Interior Back	Cover

# **GemLock**<sup>®</sup>

**GemLock** is reliable and faster to install than welding, threading or flanging, resulting in lower installation cost. Triple sealing of the C-shaped pressure responsive gasket is made from specially compounded rubber polymers with low compression set properties. Couplings perform equally well under pressure and vacuum. Couplings are available for flexible and rigid systems, and are all pre-lubricated.

#### HOUSINGS

Ductile iron housing segments conforming to ASTM-A536 Grade 65-45-12 which fully enclose the gasket. The housing keys engage into the grooves around the full pipe circumference, securing the pipe ends together with a positive grip. The housing is designed to provide the optimum combination of pressure, stress relief and end load conditions while maintaining reasonable weight and manufacturing characteristics. Every grooved pipe coupling, flange adapter and reducing coupling has a similar key section. This engages fully into the groove tying the joint integrally to the pipe.

#### GASKETS

The sealing efficiency of gaskets is such that the gasket forms an initial seal as it is stretched over the pipe ends. As the housing segments are installed and secured the pressure responsive gasket is slightly compressed to form a leak-tight joint. The strength of the seal is further enhanced by internal line pressure that creates downward pressure on the lips of the gasket. The gasket also seals well under vacuum conditions up to 10 in Hg (-0.35 Bar) which may occur when a system is drained. Please refer to the gasket selection guide for additional details and gasket materials. Gaskets are pre-lubricated for easy assembly of the coupling but should be lightly lubed for further ease of assembly and performance.

#### ROLL OR CUT GROOVED STANDARD STEEL PIPE



#### **BOLTS AND NUTS**

Oval neck track bolt conforming to ASTM A183 with minimum tensile strength of 110,000 psi or square neck carriage bolt to ASTM A446 with 120,000 psi minimum tensile strength permits tightening of the nuts from one side with a single wrench. Nuts conform to ASTM A194. Bolts and nuts are electro galvanized.

# **GemLock**<sup>®</sup>

# **FEATURES**

#### **REDUCED COST**



Coupling assembly is quick and easy. Minimal training required. The system is free from contaminates such as weld slag and pipe dope. Installation costs are controllable and estimates are more precise.

#### **UNION TYPE JOINT**



Coupling can be disassembled easily permitting maintenance and servicing of the piping system. It will facilitate periodic rotation of pipe to distribute internal wear from slurries or other abrasive media.

#### RELIABILITY



The coupling engages the pipe around the entire circumference and restrains the pipe ends from separation due to pressure and other forces, up to the maximum coupling rated working pressure.

#### **RIGID COUPLINGS**



Rigid couplings, both standard and slip-on design are available to supply a rigid, "weld-like" connection where required. These couplings are primarily used in fire protection systems, as well as when connecting piping appurtenances such as valves, strainers etc.

#### **EXPANSION AND CONTRACTION**



Flexible Coupling provides linear movement at each joint. Allows pipe expansion and contraction. Suitable for hot and cold water lines and dual temperature systems.

#### **DEFLECTION AND MISALIGNMENT**



Precise location of pipe openings through walls and floors is unnecessary. Long radius curves may be designed with fewer elbows. Useful for providing pitch for drainage. Facilitates laying pipe on rough or uneven terrain, when using flexible couplings.

#### NOISE AND VIBRATION



Slight gap between pipe ends isolates noise and vibration. Resilient gasket also helps to absorb noise and vibration. Often permits elimination of noise suppression devices.

#### **STRESS FREE JOINT - FLEXIBLE COUPLINGS**



Flexibility of the joint reduces or eliminates stresses from settlement of buried pipe or induced by seismic tremors.

# **RIGID COUPLING**

## **STYLE 5**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1" to 12"
- · Maximum Working Pressure: 300 psi

The Style 5 Coupling is our standard coupling and is designed for joint rigidity, providing a "weld like joint". Conforms to the requirements of ANSI B31.1 Power Piping Code; ANSI B31.9 Building Service Pipe Code and NFPA13 sprinkler systems. Before installing, please read the Installation Instructions on page 32.

STYLE 5



RIGID COUPLING STYLE 5													
Pi	ре	Max. Working	Allow Pipe End	Dim	nensions	(in.)	Bolt	Approx.					
Nominal Size (in.)	Actual Size (in.)	(psi)*	(in.)	Α	В	С	Size (in.)	(lb.)					
1	1.315	300	0.1	2.36	4.02	1.77	3/8 x 1-3/4	1.2					
1-1/4	1.66	300	0.1	2.76	4.17	1.73	3/8 x 1-3/4	1.31					
1-1/2	1.9	300	0.1	2.87	4.25	1.73	3/8 x 1-3/4	1.26					
2	2.375	300	0.1	3.43	4.84	1.73	3/8 x 2-3/16	1.47					
2-1/2	2.875	300	0.1	3.94	5.43	1.73	3/8 x 2-3/16	1.76					
3	3.5	300	0.1	4.61	6.54	1.77	1/2 x 2-3/8	2.41					
4	4.5	300	0.16	5.47	7.48	1.93	1/2 x 2-1/2	2.93					
5	5.563	300	0.16	6.58	8.62	1.93	1/2 x 3	3.55					
6	6.625	300	0.16	7.82	9.80	1.97	1/2 x 3	4.73					
8	8.625	300	0.19	9.96	12.60	2.32	7/8 x 4-3/4	8.15					
10	10.75	300	0.19	13.19	16.77	2.56	7/8 x 5-1/8	17.08					
12	12.75	300	0.20	14.96	18.50	2.60	7/8 x 5-1/8	24.5					



Under File No. EX15592

4

# **RIGID COUPLING - ANGLE PATTERN**

## **STYLE 5A**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1" to 12"
- · Maximum Working Pressure: 300 psi

The Style 5A Coupling is our standard coupling and is designed for joint rigidity, providing a "weld like joint". Conforms to the requirements ANSI B31.1 Power Piping Code; ANSI B31.9 Building Service Pipe Code and NFPA13 sprinkler systems. Before installing, please read the Installation Instructions on page 32.





RIGID COUPLING - ANGLE PATTERN STYLE 5A												
Pipe	e	Max. Working	Di	mensions	(in.)	Bolt	Approx.					
Nominal Size (in.)	Actual Size (in.)	Pressure (psi)*	Α	В	с	Size (in.)	Weight Each (lb.)					
1-1/4	1.66	300	2.60	4.17	1.85	3/8 x 2-3/16	1.31					
1-1/2	1.90	300	2.78	4.37	1.85	3/8 x 2-3/16	1.20					
2	2.375	300	3.35	4.86	1.85	3/8 x 2-3/8	1.47					
2-1/2	2.875	300	3.90	5.41	1.85	3/8 x 2-3/8	1.67					
3	3.50	300	4.61	6.48	1.87	1/2 x 2-1/2	2.42					
4	4.50	300	5.53	7.40	2.05	1/2 x 2-3/4	2.93					
5	5.563	300	6.60	8.62	2.05	1/2 x 2-3/4	4.40					
6	6.625	300	7.60	9.57	2.07	1/2 x 2-3/4	4.73					
8	8.625	300	9.88	12.60	2.52	5/8 x 4-3/8	8.23					
10	10.75	300	12.44	15.75	2.60	7/8 x 6-1/8	17.04					
12	12.75	300	14.82	18.27	2.60	1 x 6-1/2	21.87					

**STYLE 5A** 



UL Listed Under File No. EX15592

## **ONE-BOLT PUSH-ON COUPLING**

## **STYLE 99**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- · Bolts/Nuts: Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- · Coatings: Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- · Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1" to 6"
- Maximum Working Pressure: Schedule 10/40 365 psi, Schedule 7 300 psi

The Style 99 Push-On Coupling is an advanced rigid grooved coupling designed to connect grooved joints (whether rolled or cut) to standard grooved specifications for steel pipes. This innovative coupling utilizes two ductile iron housings that lock together with a single bolt, eliminating the need to disassemble the coupling for installation (refer to the next page for installation instructions).

This design significantly speeds up the installation process, resulting in a more economical solution for joining grooved piping and reducing overall installation costs for any grooved piping project. Before installing, please read the Installation Instructions on page 33.



ONE-BOLT, PUSH-ON COUPLING STYLE 99											
		Dim	ensions L	(in.)	Bolt Size (in.)	Weight (lbs.)					
Nominal Size (in.)	Pipe O.D. (in.)	Α	В	С							
1	1.32	2.35	4.0	1.81	3/8 x 2-3/16	1.18					
1-1/4	1.67	2.68	4.34	1.81	3/8 x 2-3/8	1.24					
1-1/2	1.9	3.0	4.60	1.81	3/8 x 2-3/8	1.30					
2	2.37	3.50	5.08	1.81	3/8 x 2-1/2	1.52					
2-1/2	2.87	3.84	5.55	1.81	3/8 x 2-3/4	1.87					
3	3.5	4.47	6.61	1.81	1/2 x 3-1/8	2.27					
4	4.5	5.60	7.72	1.89	1/2 x 3-1/8	3.09					
5	5.56	6.75	9.02	2.03	1/2 x 3-3/8	3.55					
6	6.63	8.03	10.24	2.17	1/2 x 3-1/2	5.28					





# **FLEXIBLE COUPLING**

## **STYLE 12**

- · Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- · Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature: Range: -40°F to 230°F (Service temperature range)

С

- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1" to 12"
- · Maximum Working Pressure: 300 psi

The Style 12 Coupling is our flexible lightweight coupling designed for fire protection services. Conforms to the requirements ANSI B31.1 Power Piping Code; ANSI B31.9 Building Service Pipe Code and NFPA13 sprinkler systems. Before installing, please read the Installation Instructions on page 32.

STYLE 12

В

А



UL Listed Under File No. EX15592



# **REDUCING COUPLING**

## **STYLE 25**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts**: Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1-1/2" to 8"
- · Maximum Working Pressure: 300 psi

The Style 25 Reducing Coupling allows for direct connection of two different pipe sizes, eliminating the need for two couplings and a concentric reducer. The steel washer prevents telescoping of the smaller pipe inside the larger pipe during vertical system assembly.





REDUCED COUPLING STYLE 25													
Pipe	Max. Working	Allow Allow Pipe End		on from ine	Dim	nensions	(in.)	Bolts	Approx. Weight				
Nominal Size (in.)	Pressure (psi)	Separation (in.)	Per Coup Deg.	Pipe (in.)	А	В	С	No./ Size	Each (lb.)				
1-1/2 x 1-1/4	300	0.12	1°-53'	0.4	2.88	4.55	1.77	2-3/8 x 1-3/4	1.75				
2 x 1-1/2	300	0.12	1°-33'	0.4	3.543	5.079	1.85	2-3/8 x 2-3/16	1.95				
2-1/2 x 2	300	0.12	1°-33'	0.32	3.976	5.394	1.8	2-3/8 x 2-3/16	2.50				
3 x 2	300	0.12	1°-17'	0.26	4.724	6.45	1.89	2-1/2 x 2-1/2	3.64				
3 x 2-1/2	300	0.12	1°-17'	0.26	4.72	6.457	1.89	2-1/2 x 2-1/2	3.27				
4 x 2	300	0.25	2°-38'	0.55	5.906	7.677	1.929	2-1/2 x 2-1/2	4.74				
4 x 2-1/2	300	0.25	2°-38'	0.55	5.906	7.677	1.929	2-1/2 x 2-1/2	4.55				
4 x 3	300	0.25	2°-38'	0.55	5.906	7.677	1.929	2-1/2 x 2-1/2	4.16				
5 x 4	300	0.25	2°-5'	0.44	6.969	8.74	1.909	2-5/8 x 3-1/2	6.65				
6 x 4	300	0.25	1°-44'	0.38	7.992	9.252	1.969	2-1/2 x 3	8.16				
8 x 6	300	0.25	1°-15'	0.26	10.394	12.32	2.362	2-5/8 x 4	15.15				



UL Listed Under File No. EX15592

## FLANGE ADAPTERS STYLE F190

- · Conforms to ANSI Class 125 lb. flange/ASTM CL 150
- · Available with an external threaded or grooved end
- Made of durable, high-strength ductile iron conforming to ASTM A536, Gr 65-45-12; every lot is metallurgically tested for compliance
- · Available with hot dipped galvanized coating for corrosive environments
- · Rated for 300 psi



	FLANGE ADAPTER - STYLE F190											
Nominal Size (in.)	Pipe OD D (in.)	Working Pressure (psi)	L (in.)	X (in.)	Y (in.)	Z (in.)	Bolt Size (in.) No Size					
2	2.375	300	2.56	5.98	4.74	0.63	4-5/8					
2-1/2	2.875	300	2.56	7.00	5.69	0.69	4-5/8					
3	3.500	300	2.56	7.48	6.00	0.75	4-5/8					
4	4.500	300	2.76	9.02	7.50	0.96	8-5/8					
5	5.562	300	2.76	10.00	8.50	0.96	8-3/4					
6	6.625	300	2.76	10.98	9.50	1.10	8-3/4					
8	8.625	300	3.23	13.50	11.75	1.11	8-3/4					
10	10.750	300	3.35	15.98	14.25	1.18	12-7/8					
12	12.750	300	3.54	19.01	17.00	1.26	12-7/8					



# **SemLock**<sup>®</sup>

# **GROOVED FLANGE ADAPTER**

## **STYLE 14**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 1 10,000 psi.Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Size: 2" to 12"
- Maximum Working Pressure: 2" to 8" 300 psi, 10" & 12" 175 psi

The Style 14 Flange is designed to connect ANSI Class 125 or Class 150 flange components to grooved piping systems. The use of a Style 20 Gemlock<sup>®</sup> Steel Adapter is required when used against rubber faced surfaces, serrated or irregular sealing surfaces.

#### STYLE 14

Α

**B BOLT CIRCLE** 



GROOVED FLANGE STYLE 14													
Pip	be	Max Working Pressure	Sealing S	Surface (in.)	[	Dimensions (in.)	Bolts	Approx. Weight					
Nominal Size (in.)	Actual Size (in.)	(psi) *	X Min	Y Max.	Α	B (Bolt Circle)	С	No./Size	Each (lb.)				
2	2.375	300	3.09	2.42	8.11	4.763	0.866	4-5/8 x 2-3/4	3.84				
2-1/2	2.875	300	3.58	2.92	9.055	5.511	0.866	4-5/8 x 2-3/4	5.08				
3	3.5	300	4.21	3.56	9.527	5.984	0.944	4-5/8 x 2-3/4	5.17				
4	4.5	300	5.26	4.57	11.023	7.519	0.944	8-5/8 x 2-3/4	6.46				
5	5.563	300	6.41	5.65	12.795	8.503	0.964	8-3/4 x 2-7/8	8.64				
6	6.625	300	7.48	6.71	13.583	9.5	0.964	8-3/4 x 3-1/8	8.49				
8	8.625	300	9.58	8.7	16.311	11.751	1.102	8-3/4 x 3-1/4	13.48				
10	10.75	175	11.65	10.85	20	14.25	1.195	12-7/8 x 3-1/2	24.0				
12	12.75	175	13.60	12.90	20.25	17.0	1.25	12-7/8 x4	38.0				



UL Listed Under File No. EX15592

## FLANGE ADAPTER INSERT STYLE 20

The GemLock<sup>®</sup>, "Flange Seal Ring Adapter" is designed to be used with the GemLock<sup>®</sup> Style 14, Grooved Flange. This flange ring is to be installed when using the grooved flange in conjunction with a rubber lined valve or serrated faced flange. It's purpose is to separate two rubber surfaces from coming in contact with each other, which would lead to joint failure. It is important to note that there should never be a rubber to rubber (or similar material) joint, when installing any type of pipe system.

- Carbon steel conforming to ASTM A 1011
- · Zinc electroplated standard carbon steel rings



FLAN	IGE ADAPT	ER INSERT	- STYLE 20	
Size (NPS) (in.)	A (OD) (in.)	B (ID) (in.)	Thickness (in.)	Weight (Ibs.)
2	4	2.25	.12	.30
2-1/2	4.75	2.75	.12	.40
3	5.25	3.40	.12	.42
4	6.75	4.37	.12	.69
5	7.64	5.43	.12	.75
6	8.63	6.50	.12	.84
8	10.87	8.50	.12	1.20
10	13.27	10.63	.12	1.65
12	16.0	12.65	.12	2.51

## MECHANICAL TEE -GROOVED

## **STYLE 15**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 2" to 8"
- · Maximum Working Pressure: 300 psi

Style 15 Mechanical Tee's are bolted saddle type fittings designed for fast installation of bolted branch outlets as an alternative to welding connections. Before installing, please read the Installation Instructions on page 34.

#### **Obsolete-Style 15 is being replaced by Style 35**

STYLE 15



MECHANICAL TEE - GROOVED STYLE 15												
Run Size	Outlet Size	Max. Working	Hole [ (	Diameter in.)	G Dime	iroove	d ; (in.)	Approx. Weight				
(in.)	(m.)	(psi)*	Hole Saw	Max. Perm.	Α	в	С	(lb.)				
	1-1/4	300	1.75	1.91	2.32	2.71	4.57	1.77				
2	1-1/2	300	1.75	1.81	2.32	2.71	4.57	1.70				
0 1/0	1-1/4	300	2	2.06	2.76	3.307	5.67	2.27				
2-1/2	1-1/2	300	2	2.06	2.76	3.267	5.67	2.47				
	1-1/4	300	2	2.06	2.76	3.23	5.98	2.50				
3	1-1/2	300	2	2.06	2.76	3.58	5.98	2.89				
	2	300	2.5	2.55	3.23	2.4	5.98	3.23				
	1-1/4	300	2	2.06	3.66	3.27	7.32	3.40				
	1-1/2	300	2	2.06	3.66	3.62	7.32	3.16				
4	2	300	2.5	2.55	3.66	3.82	7.4	3.30				
	2-1/2	300	3	3.10	3.82	4.84	7.4	4.55				
	3	300	3.5	3.60	3.82	4.92	7.4	4.56				
	1-1/2	300	2	2.06	4.21	3.62	8.56	4.27				
-	2	300	2.5	2.55	4.21	3.82	8.66	4.47				
Э	2-1/2	300	2.75	2.81	4.21	4.84	8.66	5.27				
	3	300	3.5	3.60	4.21	5.35	8.66	6.03				
	1-1/4	300	2	2.06	5.04	3.23	9.72	5.50				
	1-1/2	300	2	2.06	5.04	3.62	9.72	5.55				
~	2	300	2.5	2.55	5.04	3.86	9.72	6.18				
6	2-1/2	300	3.25	3.35	5.04	4.84	9.72	5.32				
	3	300	3.5	3.60	5.04	5.35	9.72	7.32				
	4	300	4.5	4.63	5.04	6.18	9.72	7.60				
	2	300	2.5	2.55	5.98	5.11	12.2	7.50				
	2-1/2	300	2.75	2.81	5.98	5.11	12.2	7.71				
8	3	300	3.5	3.60	5.98	5.39	12.2	8.3				
	4	300	4.5	4.63	5.98	6.38	12.2	9.09				

CUL US APPROVED

UL Listed Under File No. EX15592

## MECHANICAL TEE -GROOVED

#### **STYLE 35**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 2" to 8"
- · Maximum Working Pressure: 300 psi

Style 35 Mechanical Tee's are bolted saddle type fittings designed for fast installation of bolted branch outlets as an alternative to welding connections. Before installing, please read the Installation Instructions on page 34. STYLE 35

UL Listed Under File No. EX15592



	MECHANICAL ILL "OROOVED STILL 55											
Run Size	Outlet Size	Max. Working Pressure	Hole D (i	Diameter in.)	0 Dime	iroove	d s (in.)	Approx. Weight				
()	()	(psi)*	Hole Saw	Max. Perm.	А	в	с	(lb.)				
2	1-1/4	300	1.75	1.85	2.32	2.72	4.57	1.76				
2	1-1/2	300	1.75	1.85	2.32	2.72	4.57	1.69				
0 1/0	1-1/4	300	2.0	2.06	2.76	3.31	5.67	2.46				
2-1/2	1-1/2	300	2.0	2.13	2.95	3.31	5.67	2.33				
	1-1/4	300	2.0	2.06	2.76	3.23	5.98	2.50				
3	1-1/2	300	2.0	2.13	2.76	3.58	5.98	2.89				
	2	300	2.5	2.63	3.23	3.85	5.98	3.23				
	1-1/4	300	2.0	2.06	3.66	3.27	7.32	3.40				
	1-1/2	300	2.0	2.13	3.66	3.27	7.32	3.16				
4	2	300	2.5	2.63	3.66	3.82	7.40	3.30				
	2-1/2	300	2.75	2.88	3.82	4.84	7.40	4.55				
	3	300	3.5	3.55	3.82	4.92	7.40	4.56				
E	2	300	2.5	2.63	4.21	3.82	8.66	4.47				
5	3	300	3.5	3.55	4.21	5.35	8.66	6.03				
	1-1/4	300	2.0	2.06	5.04	3.23	9.72	5.50				
	1-1/2	300	2.0	2.13	5.04	3.62	9.72	5.55				
6	2	300	2.5	2.63	5.04	3.86	9.72	6.18				
0	2-1/2	300	2.75	2.87	5.04	4.84	9.72	5.32				
	3	300	3.5	3.55	5.04	5.35	9.72	7.32				
	4	300	4.5	4.63	5.04	6.18	9.72	7.60				
	2	300	2.5	2.63	5.98	3.82	12.20	7.50				
0	2-1/2	300	2.75	2.87	5.98	5.12	12.20	7.92				
o	3	300	3.5	3.63	5.98	5.40	12.20	8.30				
	4	300	4.5	4.63	5.98	6.38	12.20	9.09				

## MECHANICAL TEE -THREADED

#### **STYLE 16**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Bolts/Nuts:** Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Pre-Lubricated Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 1-1/2" to 8"
- Threads: NPT per ANSI/ASME B1.20.1
- Maximum Working Pressure: 300 psi

Style 16 Mechanical Tee's are bolted saddle type fittings designed for fast installation of bolted branch outlets as an alternative to welding connections. Before installing, please read the Installation Instructions on page 34.

#### **Obsolete- Style 16 is being replaced by Style 36**

STYLE 16



MECHANICAL TEE - THREADED STYLE 16													
Run Size	Outlet Size	Max. Working	Ho Diamet	ole ter (in.)	T Dime	hreade	d (in.)	Approx. Weight					
(in.)	(in.)	Pressure (psi)*	Hole Saw	Max. Perm.	А	В	С	Each (lb.)					
1-1/2	1	300	1.5	1.56	2.20	2.40	4.40	1.49					
	1	300	1.5	1.56	2.36	2.71	4.567	1.53					
2	1-1/4	300	2.0	2.06	2.36	2.71	4.567	1.66					
	1-1/2	300	2.0	2.06	2.36	2.71	4.567	1.88					
	1	300	1.5	1.56	2.76	3.03	5.67	1.98					
2-1/2	1-1/4	300	2	2.06	2.76	3.27	5.67	2.36					
	1-1/2	300	2	2.06	2.76	3.27	5.67	2.33					
	1	300	1.5	2.06	3.23	3.03	5.98	2.48					
2	1-1/4	300	2	2.06	3.23	3.27	5.98	2.47					
3	1-1/2	300	2	2.06	3.23	3.62	5.98	2.60					
	2	300	2.5	2.55	3.23	3.89	5.98	2.96					
	1	300	1.5	1.56	3.43	3.03	6.77	2.86					
	1-1/4	300	2	2.06	3.43	3.27	6.77	3.25					
л	1-1/2	300	2	2.06	3.43	3.62	6.77	3.25					
4	2	300	2.5	2.55	3.43	3.82	6.77	3.55					
	2-1/2	300	3.0	3.60	3.10	4.41	6.77	3.59					
	3	300	3.5	2.55	3.60	4.9	6.77	4.84					
	1-1/2	300	2	2.06	3.94	3.62	8.27	3.65					
_	2	300	2.5	2.55	3.94	3.82	8.27	3.89					
э	2-1/2	300	3.25	3.35	3.94	4.84	8.27	6.0					
	3	300	3.5	3.60	3.94	4.84	8.27	6.04					
	1-1/4	300	2	2.06	4.61	3.27	9.53	5.32					
	1-1/2	300	2	2.06	4.61	3.62	9.53	5.80					
6	2	300	2.5	2.55	4.61	3.82	9.53	5.96					
	2-1/2	300	3.25	3.35	4.61	4.84	9.53	5.31					
	3	300	3.5	3.60	4.61	5.35	9.53	7.32					
	2-1/2	300	3.25	3.35	5.75	5.11	12.2	7.48					
8	3	300	3.5	3.60	5.75	5.39	12.2	8.3					
	4	300	4.5	4.63	5.75	6.38	12.2	10.17					

e usted us APPROVED

Under File No. EX15592

## MECHANICAL TEE -THREADED

## **STYLE 36**

- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- Bolts/Nuts: Zinc electroplated carbon steel oval neck track head bolts conforming to ASTM A183 Grade 2 and SAE J429 Grade 5 with a minimum tensile strength of 110,000 psi. Zinc electroplated carbon steel heavy hex nut conforming to ASTM A536, Grade A.
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Lubrication: Supplemental lubricant is recommended for services below 0°F and for all dry pipe systems or systems to be subjected to air tests prior to being filled with water.
- Sizes: 2" to 8"
- Threads: NPT per ANSI/ASME B1.20.1
- · Maximum Working Pressure: 300 psi

Style 36 Mechanical Tee's are bolted saddle type fittings designed for fast installation of bolted branch outlets as an alternative to welding connections. Before installing, please read the Installation Instructions on page 34.

STYLE 36

UL Listed Under File No. EX15592



	MECHANICAL TEE - THREADED STYLE 36												
Run Size	Outlet Size	Max Working	Hole D (i	liameter n.)	ا Dim	Approx. Weight Each							
(in.)	(in.)	(psi)*	Hole Saw	Max. Perm.	Α	В	С	(lb.)					
	1	300	1.5	1.63	2.36	2.72	4.57	1.45					
2	1-1/4	300	1.75	1.85	2.36	2.72	4.57	1.66					
	1-1/2	300	1.75	1.85	2.36	2.72	4.57	1.88					
	1	300	1.5	1.63	2.60	3.07	5.70	1.98					
2-1/2	1-1/4	300	2.0	2.13	2.76	3.27	5.67	2.36					
	1-1/2	300	2.0	2.13	2.36	3.27	5.67	2.33					
	1	300	1.5	1.63	3.23	3.03	5.98	2.48					
2	1-1/4	300	2.0	2.13	3.23	3.27	5.98	2.47					
3	1-1/2	300	2.0	2.13	3.23	3.62	5.98	2.60					
	2	300	2.5	2.63	3.23	3.90	5.98	2.96					
	1	300	1.5	1.63	3.66	3.03	7.40	2.86					
	1-1/4	300	2.0	2.13	3.66	3.27	7.40	3.25					
	1-1/2	300	2.0	2.13	3.66	3.62	7.40	3.25					
4	2	300	2.5	2.63	3.66	3.82	7.40	3.55					
	2-1/2	300	2.75	2.87	3.66	4.41	7.40	3.59					
	3	300	3.5	3.63	3.66	4.92	7.40	4.84					
	1-1/2	300	2.0	2.13	3.94	3.62	8.66	3.65					
5	2	300	2.5	2.63	4.21	3.82	8.66	3.89					
	3	300	3.5	3.63	4.21	5.35	8.66	6.04					
	1-1/4	300	2.0	2.13	4.72	3.23	9.72	5.32					
	1-1/2	300	2.0	2.13	4.72	3.62	9.72	5.80					
6	2	300	2.5	2.63	4.72	3.86	9.72	5.96					
0	2-1/2	300	2.75	2.87	4.72	4.84	9.72	5.31					
	3	300	3.5	3.55	4.72	5.35	9.72	7.32					
	4	300	4.5	4.63	4.72	6.18	9.72	7.60					
8	4	300	4.5	4.63	5.75	6.38	12.21	10.17					



# **GemLock**<sup>®</sup>

## TEE LOCK STYLE 13\*



- **U-Bolts/Nuts:** Zinc electroplated carbon steel oval U-bolt conforming SAE J429 Grade 2. Zinc electroplated carbon steel hex flanged lock nuts conforming to ASTM A536, Grade A.
- **Coatings:**Uncoated bare ductile iron (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Gasket Material: Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Sizes: 1-1/4" to 2-1/2"
- Threads: NPT per ANSI/ASME B1.20.1
- · Maximum Working Pressure: 300 psi

Style 13 Tee Lock are designed for fast installation of bolted branch outlets.





#### \* Due to updated UL requriements the Style 13 is being replaced with the GemLock® Style 13A

	TEE LOCK STYLE 13							
Nominal	Max. Working	Hole	Din	nensions (i	n.)	Weight (lbs.)		
Size (in.)	Pressure (psi)	Saw (in.)	Α	В	С	weight (ibs.)		
1-1/4 x 1/2	300	1-3/16	1.693	3.543	2.205	0.78		
1-1/4 x 3/4	300	1-3/16	1.772	3.543	2.205	0.85		
1-1/4 x 1	300	1-3/16	1.969	3.543	2.20	0.95		
1-1/2 x 1/2	300	1-3/16	1.693	3.661	2.323	0.78		
1-1/2 x 3/4	300	1-3/16	2.126	3.661	2.323	0.89		
1-1/2 x 1	300	1-3/16	2.283	3.661	2.323	0.98		
2 x 1/2	300	1-3/16	2.126	3.780	2.323	0.82		
2 x 3/4	300	1-3/16	2.205	3.780	2.323	0.90		
2 x 1	300	1-3/16	2.598	3.780	2.323	1.02		
2-1/2 x -1/2	300	1-3/16	2.362	4.331	2.323	0.90		
2-1/2 x 3/4	300	1-3/16	2.480	4.331	2.323	0.93		
2-1/2 x 1	300	1-3/16	2.756	4.331	2.323	0.95		



## **TEE LOCK STYLE 13A\***



- Housing: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- U-Bolts/Nuts: Zinc electroplated carbon steel oval U-bolt conforming SAE J429 Grade 2. Zinc electroplated carbon steel hex flanged lock nuts conforming to ASTM A536, Grade A.
- · Coatings: Uncoated bare ductile iron (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- · Gasket Material: Grade "E" EPDM, Approved and Listed for use in Wet or Dry Systems
- Gasket Temperature Range: -40°F to 230°F (Service temperature range)
- Sizes: 1-1/4" to 2-1/2"
- Threads: NPT per ANSI/ASME B1.20.1
- · Maximum Working Pressure: 300 psi

Style 13 Tee Lock are designed for fast installation of bolted branch outlets.





#### \* Designed to meet UL's most recent flow requirements

TEE LOCK STYLE 13								
Nominal	Max. Working	Hole	Din	nensions (i	n.)	Weight (lbs.)		
Size (in.)	Pressure (psi)	Saw (in.)	Α	В	С	weight (ibs.)		
1-1/4 x 1/2	300	1-1/4	1.693	3.543	2.205	0.78		
1-1/4 x 3/4	300	1-1/4	1.772	3.543	2.205	0.85		
1-1/4 x 1	300	1-1/4	1.969	3.543	2.20	0.95		
1-1/2 x 1/2	300	1-1/4	1.693	3.661	2.323	0.78		
1-1/2 x 3/4	300	1-1/4	2.126	3.661	2.323	0.89		
1-1/2 x 1	300	1-1/4	2.283	3.661	2.323	0.98		
2 x 1/2	300	1-1/4	2.126	3.780	2.323	0.82		
2 x 3/4	300	1-1/4	2.205	3.780	2.323	0.90		
2 x 1	300	1-1/4	2.598	3.780	2.323	1.02		
2-1/2 x -1/2	300	1-1/4	2.362	4.331	2.323	0.90		
2-1/2 x 3/4	300	1-1/4	2.480	4.331	2.323	0.93		
2-1/2 x 1	300	1-1/4	2.756	4.331	2.323	0.95		

#### **STYLE 13A**

## **GROOVED FITTINGS SHORT PATTERN**

## STYLES F105, F106, F107, F135

- Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Sizes: 1-1/2" to 8"
- Maximum Working Pressure: 300 psi

Short pattern products are all full flow design, specifically for use in Fire Protection applications.





**STYLE F107** 

STYLE F135



	GROOVED FITTINGS - SHORT PATTERN								
Pip	ре	90°	Elbow No. F105	45°	45° Elbow No. F106 Equal Tee No. F107 C		Cross No. F135		
Nominal Size (in.)	Actual Size (in.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	C to E (in.)	Approx. Wgt. Ea. (lb.)
1-1/2	1.9	2.362	1.01	1.73	.78	2.362	1.34	2.75	2.5
2	2.375	2.755	1.24	2.00	1.20	2.755	1.98	2.75	2.49
2-1/2	2.875	2.992	2.03	2.24	1.63	2.992	2.82	2.99	3.19
3	3.5	3.368	2.53	2.52	2.38	3.386	3.90	3.38	5.09
4	4.5	3.996	3.74	3.00	3.84	3.996	5.72	3.99	7.22
5	5.563	4.803	7.20	3.28	5.74	4.803	9.52	4.80	7.23
6	6.625	5.61	9.06	3.51	8.11	5.5	14.13	5.5	15.97
8	8.625	6.889	20.52	4.25	14.27	6.889	27.07	6.88	28.66



# **STANDARD GROOVED FITTINGS**

## STYLES 100, 101, 102, 103, 110 & 150

- Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- · Coatings: Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Sizes: 1" to 12"
- · Maximum Working Pressure: 300 psi



STYLE 100	STYLE 102	STYLE 103	STYLE 110	STYLE 150
C to E	to E C to			

	STANDARD GROOVED FITTINGS										
Pi	Pipe		90° Elbow No. 100		2-1/2° Elbow No. 102 11-1/4° Elbow N		11-1/4° Elbow No.103 Equal Tee No.110		I Tee No.110	End	Cap No.150
Nominal Size (in.)	Actual Size (in.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	C to E (in.)	Approx. Wgt. Ea. (Ib.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	C to E (in.)	Approx. Wgt. Ea. (lb.)	L (in.)	Approx. Wgt. Ea. (Ib.)
1	1.315	2.24	.85	1.61	.45	1.38	.42	2.24	1.45	0.96	.25
1-1/4	1.66	2.755	1.17	1.732	.80	1.38	0.55	2.755	1.52	0.96	.33
1-1/2	1.9	2.755	1.17	1.732	.84	1.38	0.63	2.755	1.74	0.96	0.44
2	2.375	3.257	2.25	2.0	1.14	1.38	0.82	3.267	2.5	0.96	0.61
2-1/2	2.875	3.74	2.76	2.0	1.50	1.5	1.22	3.74	3.73	0.96	0.85
3	3.5	4.251	3.44	2.24	2.53	1.5	1.62	4.251	6.24	0.96	1.01
4	4.5	5.0	5.32	2.87	3.91	1.89	2.63	5.0	8.70	0.99	1.42
5	5.563	5.51	8.0	2.87	5.10	2.0	3.90	5.51	12.44	0.99	2.80
6	6.625	6.496	14.31	3.11	7.16	2.0	4.78	6.496	18.21	0.99	4.40
8	8.625	7.755	21.63	3.86	11.88	2.0	7.10	7.755	33.25	1.181	9.30
10	10.75	8.464	37.04	4.37	14.0	2.13	14.5	8.464	46.35	1.26	9.33
12	12.75	9.645	57.25	4.88	22.0	2.25	25.5	9.645	59.50	1.26	13.25

## **REDUCING TEE - SHORT PATTERN** STYLE 115

- Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Sizes: 2" to 10"
- · Maximum Working Pressure: 300 psi

# STYLE 115

<b>REDUCER TEE - NO. 115</b> (Add after part number the letters TF for internal or TM for external threaded outlet)							
Nominal Size (in.)	C to E (in.)	Approx. Wgt. Ea. (Ib.)					
2-1/2 x 2-1/2 x 2	3.00	5.1					
3 x 3 x 2	3.39	8.4					
3 x 3 x 2-1/2	3.39	8.6					
4 x 4 x 2	4.00	10.4					
4 x 4 x 2-1/2	4.00	11.4					
4 x 4 x 3	4.00	11.6					
5 x 5 x 2	4.80	14.5					
5 x 5 x 3	4.80	15.4					
5 x 5 x 4	4.80	16.1					
6 x 6 x 2	5.51	26.4					
6 x 6 x 2-1/2	5.51	26.5					
6 x 6 x 3	5.51	26.5					
6 x 6 x 4	5.51	29.3					
6 x 6 x 5	5.51	30.9					
8 x 8 x 2	6.90	33.5					
8 x 8 x 2-1/2	6.90	39.0					
8 x 8 x 3	6.90	33.6					
8 x 8 x 4	6.90	47.4					
8 x 8 x 5	6.90	48.3					
10 x 10 x 4	9.0	79.4					
10 x 10 x 5	9.0	78.9					
10 x 10 x 6	9.0	78.3					
10 x 10 x 8	9.0	77.2					



## **STANDARD REDUCERS** CONCENTRIC - STYLE 140 ECCENTRIC - STYLE 145

- Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- · Coatings: Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- Sizes Standard Concentric Reducer: 1-1/2" to 10" Sizes Eccentric Reducer: 3" to 10"
- · Maximum Working Pressure: 300 psi





**STYLE 140** 





CONCEN	ITRIC RI NO. 140	EDUCER )	CONCI	ENTRIC I - NO. 14	REDUCER 10
Nominal Size (in.)	E to E (in.)	Approx. Wgt. Ea. (Ib.)	Nominal Size (in.)	E to E (in.)	Approx. Wgt. Ea. (lb.)
1-1/2 x 1-1/4	2.52	.60	6 x 2-1/2	4.02	4.10
2 x 1	2.52	.72	6 x 3	4.02	4.12
2 x 1-1/4	2.52	.69	6 x 4	4.02	4.63
2 x 1-1/2	2.52	.72	6 x 5	4.02	4.35
2-1/2 x 1-1/4	2.52	.91	8 x 3	5	7.71
2-1/2 x 1-1/2	2.52	.92	8 x 4	5	6.76
2-1/2 x 2	2.52	1.02	8 x 5	5	7.71
3 x 1	2.52	1.10	8 x 6	5	8.15
3 x 1-1/4	2.52	1.15	10 x 4	5.98	20.0
3 x 1-1/2	2.52	1.16	10 x 6	5.98	14.48
3 x 2	2.52	1.21	10 x 8	5.98	14.16
3 x 2-1/2	2.52	1.25			
4 x 1	3.00	2.2			
4 x 2	3.00	2.4			
4 x 2-1/2	3.00	2.7			
4 x 3	3.00	2.8			
5 x 2	3.5	3.8			
5 x 4	3.5	2.95			
6 x 2	4.02	4.36			

ECCENTRIC REDUCER - NO. 145					
Nominal Size (in.)	E to E (in.)	Approx. Wgt. Ea. (Ib.)			
3 x 2	2.52	1.8			
3 x 2-1/2	2.52	1.6			
4 x 2	3.00	2.6			
4 x 2-1/2	3.00	2.8			
4 x 3	3.00	3.3			
5 x 2-1/2	3.50	10.8			
5 x 3	3.50	11			
5 x 4	3.50	5.1			
6 x 2-1/2	4.02	14.1			
6 x 3	4.02	14.9			
6 x 4	4.02	6.6			
6 x 5	4.02	9.4			
8 x 3	5.00	22.0			
8 x 4	5.00	22.9			
8 x 5	5.00	26.5			
8 x 6	5.00	30.8			
10 x 6	5.98	36.5			
10 x 8	5.98	38			



# **STANDARD DRAIN ELBOW**

UL Listed Under File No. EX15591

## STYLE F100D

Cast Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12

- · Fabricated Fittings: Carbon Steel Schedule 10
- · Coatings: Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- · Cast Fitting Sizes: 2" to 8"
- Threads: NPT per ANSI/ASME B1.20.1
- · Maximum Working Pressure: 300 psi

Drain Elbow comes standard with 1" female NPT outlet per ASME B1.20.1

## **DRAIN TEE STYLE 115D**

- Fabricated from ASTM A53 SCH 40 pipe
- Standard grooves to AWWA C606
- Threads are MNPT
- · Available with hot dipped galvanized coating for corrosive environments
- · Rated for 300 psi

#### **STYLE 115D**



DRAIN TEE - STYLE 115D								
Nominal	Dimer	Weight						
Size (in.)	C-E	В	(lbs.)					
1-1/4	2-3/4	2-3/4	1.4					
1-1/2	2-3/4	2-3/4	1.6					





DRAIN ELBOW - STANDARD STYLE F100D								
Pip	Dimensi	ions (in.)	Approx.					
Nominal Size (in.)	Actual Size (in.)	C to E	н	wgt. Ea. (lb.)				
2	2.375	3.27	2.75	3.8				
2-1/2	2.875	3.75	2.75	5.2				
3	3.500	4.25	2.75	5.3				
4	4.500	5.00	2.75	8.8				
6	6.625	6.50	2.75	18.7				
8	8.625	7.8	2.75	31.0				

# **STANDARD DRAIN CAP**

## **STYLE F155D**

- · Cast Fittings: Ductile Iron conforming to ASTM A536, Grade 65-45-12
- Fabricated Fittings: Carbon Steel Schedule 10
- **Coatings:** Rust inhibiting orange paint (Standard) or Hot Dipped Galvanized (Optional) conforming to ASTM A153
- · Cast Fitting Sizes: 2" to 8"
- Fabricated Fitting Sizes: 1-1/4" to 1-1/2"
- Threads: NPT per ANSI/ASME B1.20.1
- · Maximum Working Pressure: 300 psi

Drain Cap comes standard with 1" female NPT outlet per ASME B1.20.1 sizes 1-1/4" to 6" and 2" Female NPT outlet per ASME B1.20.1 on 8.

#### STYLE F155D



FIGURE F155D CAP							
Nominal Size	O.D.	End to End	Outlet Size	Approx. wgt. Ea.			
in./DN	in.	in.	in.	lbs.			
1-1/4	1.660	1-1/4	1	0.4			
1-1/2	1.900	1-1/4	1	0.5			
2	2.375	1	1	0.5			
2-1/2	2.875	1	1	0.7			
3	3.500	1	1	1.1			
4	4.500	1-1/8	1	2.8			
5	5.563	1-1/8	1	4.0			
6	6.625	1-5/16	1	6.0			
8	8.625	1-1/2	2	12.5			



# **90° ADAPTER ELL**

## **STYLE 105TL**

- Transitions from grooved to threaded connection
- · Direct connection to sprinkler heads
- Available in rust inhibitive black paint & galvanized finish
- Made of durable, high-strength ductile iron conforming to ASTM A536, Gr 65-45-12; every lot is metallurgically tested for compliance
- Rated for 500 psi



90° ADAPTER ELL							
Nominal Sizo (in )	Max Work Prossure (psi)	Dimensions (in.)					
Nominal Size (m.)	Max. Work Pressure (psi)	А	В				
1-1/4 x 1/2	500	1.77	1.20				
1-1/4 x 3/4	500	1.77	1.20				
1-1/4 x 1	500	1.91	1.24				
1-1/2 x 1/2	500	1.77	1.32				
1-1/2 x 3/4	500	1.77	1.32				
1-1/2 x 1	500	1.91	1.32				
2 x 1/2	500	1.75	1.57				
2 x 3/4	500	1.77	1.57				
2 x 1	500	1.91	1.63				
2-1/2 x 1/2	500	1.75	1.75				
2-1/2 x 3/4	500	1.75	1.75				
2-1/2 x 1	500	1.91	1.81				



#### STYLE 105TL

#### LANSDALE<sup>®</sup> GROOVED END SWING VALVE MANUFACTURING CORP. CHECK VALVE



## **MODEL LVCVGG-400**

- Leak-Tight Sealing: Equipped with an EPDM non-stick rubber ring for reliable, leak-tight sealing corrosion resistance: All wetted parts are made from stainless steel, providing superior corrosion resistance.
- **Durable Coating:** Both the interior and exterior surfaces are coated with a fusion-bonded coating that meets or exceeds the AWWA C550 Standard
- · Pressure Rating: Rated for 400 PSI across all sizes
- · Certification: UL Listed and FM Approved for safety and reliability in fire protection applications
- Body: Ductile Iron (ASTM A536)
- Seat Ring: Brass (ASTM C37700)
- Clapper: Stainless Steel (ASTM A240)
- Rubber Ring: EPDM
- Spring: Stainless Steel (ASTM A240)
- Hinge Pin: Stainless Steel (ASTM A240)

The LVCVGG-400 Grooved End Swing Check Valve is engineered for reliability and efficiency in fire protection systems. It is designed to be installed in either horizontal or vertical lines with upward flow, offering versatility in various installation scenarios. The valve features a low pressure drop and is easier and faster to maintain and install compared to traditional valves.





DIMENSIONS								
Nominal Valve Size (In.) (DN)	Pipe OD		Weight					
	(In.)	Α	В	С	D	E	F	(Lbs.)
2	2.37	6.34	3.54	2.80	5.02	2.37	4.21	6.24
2-1/2	2.88	7.06	3.91	3.19	5.71	2.87	4.74	8.80
3	3.5	7.80	4.29	3.61	6.44	3.5	5.24	13.23
4	4.5	8.62	4.06	4.25	7.71	4.50	6.49	19.84
6	6.63	10.38	5.12	5.43	9.56	6.63	8.00	37.48



# LANSDALE\* GROOVED END CHECK VALVE WALVE WITH INSPECTION COVER



## MODEL LVCVGG-RF

- Grooved connections are cut in accordance with AWWA C606
- Maximum Working Pressure: 300 psi
- Removable inspection cover
- Spring assisted clapper









MATERIAL SPECIFICATION					
Part NO.	Part	Material	ASTM Specification		
1	Body	Ductile Iron	ASTM A536 Gr. 65-45-12		
2	Cover	Ductile Iron	ASTM A536 Gr. 65-45-12		
3	Cover Gasket	Rubber	D2000 EPDM		
4	Bolts & Washers	Carbon Steel	ASTM A307 Gr. B		
5	Clapper Facing	Rubber	D2000 EPDM		
6	Clapper 2"- 8"	Stainless Steel	ASTM A276 Gr. 304		
ю	Clapper 10"- 12"	Ductile Iron	ASTM A536 Gr. 65-45-12		
7	Retaining Disc	Stainless Steel	ASTM A276 Gr. 304		
8	Locknut	Stainless Steel	ASTM A276 Gr. 304		
9	Spring	Stainless Steel	ASTM A276 Gr. 304		
10	Retaining Ring	Stainless Steel	ASTM A276 Gr. 304		
11	Hinge Shaft	Stainless Steel	ASTM A276 Gr. 304		

NOMINA	NOMINAL PIPE SIZE			MINA	L DIM	ENSIC	ONS	
Valve Size (in.)	PIPE O.D./ (in.)	Α	в	С	D	Е	F	J
2	2.38	6.75	4.10	2.48	2.17	3.27	4.76	1.63
2-1/2	2.88	8.00	4.57	2.76	2.76	3.86	5.87	1.65
3	3.50	8.37	5.35	3.11	3.15	3.86	5.87	1.65
4	4.50	9.63	6.30	3.98	3.62	4.53	7.13	1.81
5	5.56	10.50	7.40	4.46	4.13	4.90	7.50	1.75
6	6.63	11.50	7.87	5.59	4.53	5.00	7.60	1.85
8	8.63	14.00	9.92	6.85	5.51	5.43	8.46	2.13
10	10.75	18.00	12.38	8.62	6.41	7.50	10.50	3.00
12	12.75	21.00	14.28	9.93	7.27	7.62	10.62	2.75

#### LANSDALE<sup>®</sup> VALVE MANUFACTURING CORP. RISER CHECK ASSEMBLY (SHOT GUN RISER)



- Meet or exceeds the requirements of UL 312 and FM 1210 standard
- Spring loaded for fast closure
- · Drain plug at the bottom under the inlet end for attaching a drain valve
- Excellent flow characteristics
- Superior design featuring exceptionally low pressure losses at high flow rates Rubber disc facing and bronze seat ring
- Grooved connections are cut in accordance with AWWA C606 standard grooved specifications for steel pipe
- UL 312/ULC listed and FM 1210 approved
- Fusion bonded coating interior and exterior meet or exceed all applicable of AWWA C550 standard
- 350 psi rated @ 0° C to 87° C

Lansdale's Riser Check Valve Assemblies are intended for use in wet pipe fire protection systems, as well as preaction systems where there is no need for a mechanical alarm. The use of a water flow switch can provide an electronic alarm. Grooved end connections provide fast and economical installation of a UL/FM Approved coupling, such as GemLock<sup>®</sup>. When installed vertically the direction of flow arrow should point upward. For horizontal installation, the hinge pin must be located at the top. If used in preaction system the valve must be installed vertically.



MAIN DIMENSIONS (in.)								
Size	1.25	1.5	2	2.5	3	4	6	8
L	6.3	6.3	6.7	7.2	7.8	8.6	10.62	12.8
н	2.5	2.5	3	3.13	3.5	4	5	6.3



MA	MATERIAL SPECIFICATIONS					
Part NO.	Material	ASTM Specification				
Body	Ductile Iron	A536 Grade 65-45-12				
Body Seat Ring	Bronze	B62 C83600				
Disc	Stainless Steel	A351 Grade CF8				
Disc Facing	Rubber	D2000 EPDM				
Spring	Stainless Steel	A276 Grade 302				
Hinge Pin	Stainless Steel	A276 Grade 304				
Disc Facing Bolt/Nut	Stainless Steel	A276 Grade 304				
Angle Drain Valve	Bronze	B148 C95500				
3-Way Valves	Bronze	B148 C95500				
Nipples	Stainless Steel	A276 Grade 304				
Air/Water Gauges	_	_				



# **GemLock**® LANSDALE\* GROOVED BUTTERFLY

c(UL)us EX15837



## MODELS LVBG1 (2" - 8") & LVBG3 (10" - 12")

VALVE

Model LVBG1 Rated 300 psi

MANUFACTURING CORP.

- Model LVBG3 Rated 175 psi
- Indoor/Outdoor use
- · Prewired double tamper switches/Normally Open
- Available Normally Closed
- · Eliminates water hammer
- · Slow open/slow close
- Flag type position indicator
- · DI body encapsulated with a resistant durable polymer coating to ensure a long service life
- · Disc is EPDM coated with SS stem

The Lansdale's grooved butterfly valve is an NFPA compliant valve designed and manufactured for the Fire Protection industry and used as a control or isolation valve within the fire protection system. See Lansdale's Installation & Maintenance Manual for electrical schematics.



HANDWHEEL	INDICATOR FLAG				
1/2 NPT CONDUIT CONNECTION					
	DISC				
→ <	A →				

DIMENSIONAL DATA (in.)												
Nominal Valve Size (In.) (DN)	Pipe OD	Α	в	С	D	Е	F	G	н	I	Wgt. (Ibs.)	N
2	2.37	3.8	10.63	2.85	4.90	4.92	4.28	1.99	0	0	9.6	1
2-1/2	2.88	3.8	11.72	3.35	5.5	4.92	4.28	1.99	0	0	11.24	
3	3.5	3.8	12.22	3.58	5.76	4.92	4.28	1.99	0	0	12.57	2
4	4.5	4.54	13.92	4.29	6.75	4.92	4.28	1.99	0	0	15.65	3
5	5.56	5.21	16.0	5.16	7.93	5.91	5.79	2.44	0	0	25.8	
6	6.63	5.21	17.01	5.71	8.44	5.91	5.79	2.44	0	0	29.32	4
8	8.63	5.8	19.02	6.69	9.29	8.86	5.79	2.44	5.07	0.95	49.6	5
10	10.75	6.26	22.46	7.68	11.1	8.86	8.19	2.91	7.21	1.65	73.41	
12	12.75	6.5	25.39	9.5	12.2	8.86	8.19	2.91	9.96	2.7	89.29	6

MATERIAL LIST						
NO.	Description	Material	Specification			
1	Body	Nylon-11 Coated	ASTM A536			
2	Disc	EPDM Encapsulated	ASTM A536			
3	Stem	Ductile Iron	ASTM A536			
4	Signal & Gearbox	Ductile Iron	AISI410			
5	Hand wheel	Ductile Iron	ASTM A536			
6	O-ring	EPDM	ASTM A536			

### LANSDALE\* POWERBALL 300 VALVE MANUFACTURING CORP. SPRINKLER CONTROL VALVE



UL Listed Under Lansdale: HMER. EX15837

Sprinkler Control Valve for indoor and outdoor use. Brass body, chrome plated brass disc, and 300 Psi. UL Listed/FM Approved. Available threaded in sizes 1" to 2-1/2" and grooved from 1-1/4" to 2-1/2". Complete with position indicator and integral tamper switch.

- Internal tamper switch for Indoor/Outdoor Use.
- · Flag type indicator
- Prewired double tamper switch
- · Elimination of water hammer
- Slow opening and closing



See Lansdale's Installation & Maintenance Manual for electrical schematics.

POWERBALL GROOVED				
Size (in.)	Weight			
1-1/4	3.90			
1-1/2	4.12			
2	4.78			
2-1/2	6.17			

POWERBALL THREADED				
Size (in.)	Weight			
1	3.42			
1-1/4	3.75			
1-1/2	4.03			
2	5.18			
2-1/2	7.46			

DIMENSIONS					
Size (in.)	1-1/4	1-1/2	2	2-1/2	
А	3.86	4.02	4.09	4.49	
н	5.20	5.47	6.07	6.58	

MATERIAL LIST					
No.	Name	Material List			
1	Body	Bronze ASTM 584 C83600			
2	Disc	SS304			
3	Hand wheel	ASTM A216 WCB			
4	Seat	ASTM D2000 VITON			
5	Indicator	Powder Metal FD0205 95HT			
6	Housing	Brass ASTM B16 C36000			
7	Cover	Brass ASTM B16 C36000			

## **PI TAPE INSTRUCTIONS**

#### **GROOVE DIAMETER**

Make sure the groove and gasket sealing area (A Dim) are clean, smooth and free of any surface imperfections. Wrap a Go-NoGo Pi Tape around the groove, overlapping the tape as shown making sure the tape is in the groove and not twisted. The arrow should be within the **Groove Diameter Range** for the pipe size, if the arrow falls outside this range the groove is out of spec and the grooving tool should be adjusted.



#### MAXIMUM FLARE DIAMETER

Wrap a Go-NoGo Pi Tape around the end of the pipe as shown, overlapping the tape as shown and making sure that the tape is not twisted. The arrow must fall between the **Pipe OD Range** band and the **Max Flare Line**. The groove is out of spec if the arrow falls outside the **Max Flare Line**.



#### **OD PIPE DIAMETER**

Wrap a Go-NoGo Pi Tape around the pipe OD (away from the groove), making sure that the pipe is clean and free of any rust, dirt, welding beads etc, overlapping the tape as shown and making sure that the tape is not twisted. The arrow must fall within the **Pipe OD Range** to be within spec, if the arrow falls outside this range the pipe is out of spec and must be replaced.



GROUVED STEEL PIPE DIMENSIONS								
Nominal Pipe Size (in.)	Actual OD (in.)	Pipe OD		Groov	Max.			
		Max. (in.)	Min. (in.)	Max. (in.)	Min (in.)	Flare Dia. (in.)		
3/4	1.050	1.060	1.040	0.938	0.923	1.15		
1	1.315	1.328	1.302	1.190	1.175	1.43		
1-1/4	1.660	1.676	1.644	1.535	1.520	1.77		
1-1/2	1.900	1.919	1.881	1.775	1.760	2.01		
2	2.375	2.399	2.351	2.250	2.235	2.48		
2-1/2	2.875	2.904	2.846	2.720	2.702	2.98		
3	3.500	3.535	3.469	3.344	3.326	3.60		
3-1/2	4.000	4.040	3.969	3.834	3.814	4.10		
4	4.500	4.540	4.469	4.334	4.314	4.60		
5	5.563	5.619	5.532	5.395	5.373	5.66		
6	6.625	6.688	6.594	6.455	6.433	6.73		
8	8.625	8.688	8.594	8.441	8.416	8.80		
10	10.750	10.813	10.719	10.562	10.535	10.92		
12	12.750	12.813	12.719	12.531	12.501	12.92		



## **GROOVING SPECIFICATIONS**



PIPE GROOVING SPECIFICATIONS												
1 Nominal Size (in.) Actual Size	2 Pipe Outside Diameter OD (in.)		3 Gasket Seat	4 Groove Width B (in.)		5 Groove Diameter C (in.)		6 Groove Depth Bef	7 Min. Allowable Wall Thickness (in.)		8 Max. Allowable	
	Actual Size	Toler	ance	A (III.)	Roll Groove	Cut Groove	Actual Size	Toler.	D (in.)	Roll Groove	Cut Groove	(in.)
1	1.315	0.013	0.013	0.625	0.281	0.313	1.190	0.015	0.063	0.065	0.133	1.43
1-1/4	1.660	0.016	0.016	0.625	0.281	0.313	1.535	0.015	0.063	0.065	0.140	1.77
1-1/2	1.900	0.019	0.019	0.625	0.281	0.313	1.775	0.015	0.063	0.065	0.145	2.01
2	2.375	0.024	0.024	0.625	0.344	0.313	2.250	0.015	0.063	0.065	0.154	2.48
2-1/2	2.875	0.029	0.029	0.625	0.344	0.313	2.720	0.018	0.078	0.083	0.188	2.98
3	3.500	0.035	0.031	0.625	0.344	0.313	3.344	0.018	0.078	0.083	0.188	3.60
4	4.500	0.045	0.031	0.625	0.344	0.375	4.334	0.020	0.083	0.083	0.203	4.60
4-1/2	5.000	0.050	0.031	0.625	0.344	0.375	4.834	0.020	0.083	0.095	0.203	5.10
5	5.563	0.056	0.031	0.625	0.344	0.375	5.395	0.022	0.084	0.109	0.203	5.66
6	6.625	0.063	0.031	0.625	0.344	0.375	6.455	0.022	0.085	0.109	0.219	6.73
8	8.625	0.063	0.031	0.750	0.469	0.438	8.441	0.025	0.092	0.109	0.238	8.80
10	10.750	0.063	0.031	0.750	0.469	0.500	10.562	0.027	0.094	0.134	0.250	10.92
12	12.750	0.063	0.031	0.750	0.469	0.500	12.531	0.030	0.109	0.156	0.279	12.92

#### Column 1

Nominal IPS pipe outside diameter.

#### Column 2

Maximum deviation from square cut ends for 1.25" thru 3" is 0.03"; for 4" thru 6" is 0.045" and for 8" and above is 0.06".

#### Column 3

To provide a lock tight seal, the gasket seating area on pipe shall be free of roll marks, indentations, paint scale, dirt, chips, grease, rust and etc.

#### Column 4

Groove width. Groove bottom to be free from loose dirt, chips, rust and scales. Bottom of grooves to be radius and the vertical wall of grooves must provide at least 0.03" vertical side for proper assembly of couplings.

#### Column 5

Groove outside diameter. The groove must be concentric to the pipe circumference. Groove must be within the diameter tolerance indicated.

#### Column 6

Groove depth. For reference only. Refer to Column 5.

#### Column 7

Minimum allowable wall thickness to which the pipemay be roll grooved or cut grooved.

#### Column 8

Maximum allowable pipe and flare diameter. Measured at the most extreme pipe ends.

# **GemLock**<sup>®</sup>

## INSTALLATION AND ASSEMBLY INSTRUCTIONS FOR RIGID COUPLING STYLE 5 & FLEXIBLE COUPLING STYLE 12

Step 1. Check & Lubricate Gasket

Apply a thin coating of lubricant to the exterior surface and sealing lips of the EPDM gasket. Be careful that foreign particles do not adhere to lubricated surfaces.



Step 2. Gasket Installation Slip the gasket over the pipe end making sure the

gasket lip does not over-

hang the pipe end.



#### Step 3. Alignment

After aligning the two pipe ends, pull the gasket into position centering it between the groove. It should not extend into the groove on either pipe.





Step 4. Housings Place the coupling housing halves over the gasket making sure the housing keys engage the grooves. Insert the bolts and turn nuts finger tight.



#### Step 5.

Tighten the nuts alternately and equally until there is a small gap of approximately 1/16 of an inch.

**CAUTION:** Uneven tightening may cause the gasket to pinch.

NOTE: Flexible couplings should be tightened bolt pad to bolt pad.



#### Step 6. Assembly is Complete

Visually inspect the pipe joint to assure the coupling keys are fully engaged in the pipe grooves and the bolt pads have equal gaps.



Nuts should be securely tightened but no specific torque specified.

# **GemLock**<sup>®</sup>

## **GEMLOCK® ONE-BOLT, PUSH-ON COUPLING** STYLE 99 INSTALLATION INSTRUCTIONS

**Step 1.** Inspect exterior groove and ends of the pipe to verify all burrs, loose debris, dirt, chips, paint and any other foreign material such as grease are removed. Pipe end sealing surfaces must be free from sharp edges, projections, indentations, and/or other defects.

**Step 2.** Do not remove the nut from the bolt. Open the coupling by extending the coupling segments out to the extent allowed by the bolt and nut.

**NOTE:** The GemLock® Style 99 coupling, comes with a pre-lubricated EPDM-A gasket and it is recommended that lubricant such as Lansdale's, LansLube, be applied onto the visible portion of the gasket at the bolt pad. Additionally, it is recommended to use a silicon based lubricant in dry pipe and freezer systems.

**Step 3.** Push the gasket/coupling onto one end of the pipe until the positioning-plate of the gasket is in contact with the end of the pipe (**SEE FIGURE 1**) the red highlight is the positioning-plate. The pipe end should not cross through the positioning-plate of the gasket. (**SEE FIGURE 2**).





**Step 5.** Tighten nut to the recommended bolt torque. **(SEE NOTE BELOW)** Visually inspect the coupling to ensure that the housing keys are engaged into the pipe grooves.

	r	CORRECT	INCORRECT
SIZE (in.)	SPECIFIED BOLT TORQUE		
1-2	60-75 ft-lbs.		
2-1/2	65-80 ft-lbs.		
3	80-95 ft-lbs.		
4	90-115 ft-lbs.		
5-6	100-120 ft-lbs.		

#### NOTE:

When fully tightened a small gap of approximately 1/16" should exist between the bolt pads. Bolt-torque information is supplied as a guideline and may be used when setting the torque on power impact wrenches. Refer to the manufacturer's instructions for settings. Bolt lengths require the use of deep sockets.

#### CAUTION:

Removal of the nut from the bolt may result in the coupling segments separating at the hinges and the coupling disengaging from the pipe. Use caution to avoid equipment damage and/or personal injury. Do not leave coupling unattended on a single pipe end as it may disengage from the pipe. Failure to do so may result in equipment damage and/or personal injury.



Scan for Video

Step 1.



Step 2.



/ -Lubricate here

Step 3.



Step 4.



Step 5.



## **GEMLOCK MECHANICAL TEE** INSTALLATION INSTRUCTIONS

**Step 1.** Make sure the correct hole saw size is being used. Holes must not be drilled on the weld of the pipe. Ensure that 5/8 inch area around the hole is clean, remove any burrs, rust, grease or dirt.



**Step 2.** Inspect the sealing surface of the gasket to make sure no debris is present. Lubricate the exposed sealing surface of the gasket, with Lanslube.



**Step 3.** Put gasket in the Mechanical Tee making sure the gasket lines up with the tab recesses in the housing.



**Step 4.** Install the Mechanical Tee in the hole, making sure it is centered.



**Step 5.** Install the bottom piece and make sure the locating collar engages the outlet hole properly. Check this engagement by rocking the upper (outlet) housing in the hole. Tighten nuts by hand to hold the MT in place.



**Step 6.** Tighten the nut evenly by alternating sides until the specified torque values are achieved.



#### WARNING:

- 1. It is important to tighten the nuts evenly by alternating sides to prevent gasket pinching.
- 2. Proper torquing of bolts is required to obtain specified performance. Over torquing may result in bolts or cast breaking.

BOLT SIZE	WEIGHT
(in.)	lbsft.
3/8	30-45
1/2	80-100
5/8	100-130
3/4	130-180
7/8	180-240

# **GemLock**<sup>®</sup>

#### **GASKET DATA STANDARD IPS GASKETS** GRADE Е -40°F TO +230° F **TEMPERATURE RANGE** -40°C to + 110° C COMPOUND EPDM CONFORMING TO ASTM D2000 (2CA615A25B24F17Z) Recommended for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services. UL classified in accordance with ANSI/NSF 61 for cold -30°F (-34°C) **GENERAL SERVICE** RECOMMENDATIONS and hot +230°F (+110°C) Potable water service. Not recommended for petroleum services. Acetaidehyde **Borddeaux Mixture** Ethyl Alcohol Mercuric Cynaide Sodium Bicarbonate Acetic Acid up to 10% Boric Acid Ethyl Cellulose Mercury Sodium Bisulphate Butanol (see Butyl 100°F (38°C) Ethyl "Cellusolve" Methyl Acetate Sodium Bisulphite (black Alcohol) Ethyl Chloride Acetic Anhydride Methl Alcohol, Methanol liquor) **Butyl Acetate** Sodium Bromide Ethyl Oxalate Acetone Methyl Cellosolve (Ether) **Butyl Acetyl Ricinoleate** Acetophenone Ethylene Chlorohydrin Methyl Ethyl Ketone Sodium Chlorate **Butyl Alcohol** Ethylene Glycol Methl Formate Sodium Chloride Acetylene Butyl "Cellosolve Alkalis Ferric Chloride to 35% Methyl Isobutyl Carbionol Sodium Cynaide Adipate" Methyl Isobutyl Ketone Sodium Hydroxide, Allyl Alcohol to 96% Ferric Chloride, Satu-**Butyl Phenol** Nickel Chloride to 50% Aums rated **Butylene Glycol** Ferric Hydroxide Sodium Hypochlorite, Aluminum Chloride Nickel Nitrate Calcium Chloride Aluminum Fluoride Fluboric Acid Nickel Plating Solution to 20% Calcium Hydroxide Fly Ash 125°F (52°C)-Max. Sodium Metaphosphate Aluminum Hydroxide Aluminum Nitrate (Lime) Foam Nitric Acid, to 10%, Sodium Nitrate Aluminum Phosphate Calcium Hypochlorite Formaldehyde 75°F-(24°C)-Max. Sodium Peroxide Calcium Hypochlorite Aluminum Salts Formic Acid Nitric Acid, to 10%, Sodium Phosphate Calcium Hypochloride Aluminum Sulfate Freon 134a, 176°F 75°F- (24°C)-Max. Sodium Silicate Calcium Nitrate Ammonia Gas, Cold (80°C) Nitrous Oxide Sodium Suphide Calcium Sulfide Fumaric Acid Sodium Sulphite Solution, Ammonia Gas, Hot **Oxalic Acid** Ozone Carbotol Furfuryl Alcohol to 20% Ammonia, Liquid Carbon Dioxide, Dry Sodium Thiosulphate, Ammonium Carbonate Glue Phosphate Ester Carbon Dioxide, Wet "Hypo" Stannous Chlo-Glycerin Phosphoric Acid to 75% & Ammonium Fluoride Carbon Monoxide Glycerol ride, to 15% Ammonium Hydoxide 70° F (21ºC)-Max Ammonium Metaphosphate Caustic Potash, Glycol Potassium Bromide Starch **Cellosolve Acetate** Glycolic Acid Ammonium Nitrate Potassium Carbonate Sulphur Ammonium Persulfate Cellosolve (Alcohol Halon Potassium Chloride Sulphuric Acid, to 25%, Ether) 150°F (66°C)-Max. to10% Hexaldehyde Plating Solutions (gold, Cellulube 220 Hydrobromic Acid to **Tributyl Phosphate** Ammonium Sulfate brass, cadmium, copper, (Tri-Aryl-Phosphate) 40% Triethanolamine Ammonium Sulfide lead, silver tin, zinc) Ammonium Thictnate Cellulube Hydraulic Hydrochloric Acid to Potassium Cyanide Trisodium Phosphate Ammonium Thioynate Fluids 36% Potassium Ferricynanide Urea Chloric Acid to 20% Amyl Acetate 75°F (28.9°C) Potassium Ferrocynanide Vinyl Acetate Hydrocyamic Acid Chlorine, Water Potassium Iodide White Liquor Amyl Alcohol Chloroacetic Acid Hydrogen Gas, Cold Zinc Sulphate Aniline Potassium Nitrate Chloroacetone Hydrogen Gas, Hot Aniline Dyes Potassium Permanganate, Citric Acid Aniline Hydrochloride Hydrogen Sulfide, saturated to 25% **Copper Flouride** Hydroxylamine Sulfate, Potassium Sulphate Aniline Oil Copper Nitrate Antimony Chloride Hydrochlorous Acid, Propanol Antimony Trichloride Copper Sulfate Dilute **Propyl Alcohol** Cyclohexanone Isobutyl Alcohol Propylene Glycol Argon Gas Deionized Water Isopropyl Acetate **Barium Carbonate** Proguard 55 **Dibutyl Phialate** Barium Chloride Isopropyl Alcohol Pyrrole

**Diethyl Sewbacate** 

**Diethylene Glycol** 

**Dioctyl Phthalate** 

Dowtherm SR-1

Ethyl Acetoacetate

Ethanolamine

Diozne

Barium Hydroxide Benzaldehyde

Benzoic Acid

Borax

Benzyl Alcohol

Benzyl Benzoate

Bleach, 12% Active CP

Ketones

Lead Chloride

Lime and H2O

Magnesium Chloride

Magnesium Sulfate

Mercuric Chloride

Magnesium Hydroxide

Salicylic Acid

Silver Nitrate

Carbonate

Ester

Silver Cyanide

Skydrol 500 Phosphate

Soda Ash, -Sodium

# **GemLock**<sup>®</sup>

FIRE PROTECTION PRODUCTS CROSS REFERENCE CHART								
PRODUCT	GEMLOCK®	VICTAULIC®	<b>GRUVLOK</b> <sup>®</sup>	ANVIL STAR <sup>®</sup> (SPF)	TYCO®			
Rigid Coupling	5	—	7400	C-4	577			
Rigid One-Bolt Push-On Coupling	99	009, 109	74 FP	_	579			
Rigid Coupling - Angle Pattern	5 <b>A</b>	005	_	—	_			
Light Flexible Coupling	12	75	7000	C-3	705			
Reduced Coupling	25	750	7010	RC-2	716			
Groove Split Flange	14	744	7012	F-3	71			
Flange Adapter Nipple	F190	41	7788	F-2	341			
Mechanical Tee with Grooved Outlet	15,35	920	7046	MT-2, MT-2A	730			
Mechanical Tee with Threaded Outlet	16, 36	920	7045	MT-1, MT-1A	730			
Tee Lock	13	922	_	MT-30	522			
Short Pattern 90° Elbow	F105	001	7450	SE-1	510S			
Short Pattern 45° Elbow	F106	003	7051	E-2	501			
Short Pattern Straight Tee	F107	002	7460	ST-1	519S			
Short Pattern Reducing Tee	115	25	7061	T-2	221			
Short Pattern Cross	F135	35	7068	X-1	327			
Standard 90° Elbow	100	10	7050	E-1	510			
Standard 22-1/2° Elbow	102	12	7052	E-3	212, 312, 512			
Standard 11-1/4° Elbow	103	13	7053	E-4	211, 311, 511			
Standard Tee	110	20	7060	T-1	516			
Standard Cap	150	006	7074	K-1	260			
Concentric Reducer	140	50	7072	R-1	250, 550			
Eccentric Reducer	145	51	7073	R-2	_			
Drain Elbow	F105D	10DR	7050DR	E-9	510DE			
Drain Cap	F155D	_	_	К-9	_			
Adapter Reducing Elbow 90° GRV x THD	105TL	67	SE-5	-	6			

Victaulic® - Registered Trademark of Victaulic Company of America.

Gruvlok<sup>®</sup> - Registered Trademark of ASC Engineered Solutions™.

AnvilStar® - Registered Trademark of ASC Engineered Solutions™

# **TERMS: NET 30 DAYS**

This Limited Warranty protects the Buyer from manufacturer defects in all products sold by GemLock ("Company") to Buyer ("Covered Products") for a period of one (1) year from delivery of the Covered Products to Buyer or to a location specified by Buyer (the "Warranty Period").

During the Warranty Period, Company will repair or replace (at Company's soleoption) any Covered Products at no charge if after evaluation such Covered Products are deemed by Company to be of defective manufacture and unusable for ordinary purposes. This shall be Buyer's sole remedy for defects.

This Limited Warranty applies only to manufacturer defect in Covered Products used under normal operation, and does not cover defects caused in whole or part by installation, project design or any other external factors. Any misuse, abuse, or unauthorized repair or modification of or affecting the Covered Products, or failure to follow manufacturer instructions or recommendations, shall void this Limited Warranty.

UNLESS SPECIFICALLY NEGOTIATED IN A SEPARATE WRITING, COMPANY OFFERS NO OTHER WARRANTIES, EXPRESS OR IMPLIED,INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. In no event shall Company be responsible for any special, punitive, incidental, consequential or indirect damages of any kind, damages exceeding the price of any defective Covered Products, or any removal or reinstallation costs.

To obtain warranty service, Buyer must contact Company within ten (10) days of when it becomes aware of a warranty issue, but in no event later than three hundred seventy five (375) days from delivery of the Covered Products to Buyer. This Limited Warranty is transferable only with written consent of Company.



# **GROOVED PRODUCTS**

www.gemlockgrooved.com